ATE SUPER DOT 5.1

The new premium liquid that meets the highest demands

The new premium brake fluid from ATE sets technological standards. It combines a high wet boiling point of 180°C and outstanding viscosity at very low temperatures, something that previously available brake fluids could not achieve. With a maximum of 750 mm²/sec. at -40°C, the viscosity values of ATE Super DOT 5.1 even exceed those of ISO Class 6 – well above the specifications for DOT 5.1 class brake fluids.

Benefits & Features

- I Optimal for ESP®, ABS and ASR: low viscosity even at low temperatures, providing fast reaction times especially in the low temperature range (down to -40°C)
- I Exceeds legal and technical requirements with very good flowability, a high wet boiling point and excellent viscosity values
- I Ideal for all applications and optimal functionality in hot as well as cold conditions
- I Meets OEM requirements
- I Protects against corrosion thanks to high-quality additives

Technical Data

- I DOT 5.1 (glycol-based)
- I Boiling point: 265 °
- I Wet boiling point: 180 °
- I Viscosity 750 mm²/sec.
- I Replacement interval up to 3 years, depending on use
- I Container sizes: 1LI Available from Q4/2020
- Container sizes: 1L



ATE Part No.	Description	Size
706602	Super DOT 5.1	1 Liter

Properties

Boiling Point	Wet Boiling Point	Viscosity at	Change Interval
°C / °F	°C / °F	-40 °C mm² /s	
min. 265 °C / 509 °F	min. 180 °C / 356 °F	max. 750 mm2/s	up to 3 years

- I ATE Super DOT 5.1 complies with international specifications. It is available in the familiar metal cans in liter size.
- I ATE Super DOT 5.1 is a glycol ether-based brake fluid. It must never be mixed with silicone-based DOT 5 class brake fluids.

Continental Automotive Systems

6755 Snowdrift Road Allentown, PA - USA 18106 Tech Support: 800-265-1818 | salessupport-us@ate-na.com | www.ate-na.com

